

Codes & Guidelines

Series 750

Push-up or electric operation.

Maximum opening width is 10'-0".

Maximum opening height is 12'-0".

26 gauge curtain with windlocks on curtain for opening widths over 6'-0".

Florida state approval number FL2274-R2.

Not for use in HVHZ.

Series 850-S

Push-up or electric operation.

Maximum opening width is 8'-8".

Maximum opening height is 12'-0".

26 gauge curtain with windlocks on curtain for all opening widths.

Florida state approval number FL 2274-R2.

For use in HVHZ, other than Miami-Dade County.

Series 850

Push-up or electric operation.

Maximum opening width is 8'-8".

Maximum opening height is 12'-0".

24 gauge curtain with windlocks on curtain for all opening widths.

Miami-Dade County NOA number 05-0623.04.

For use in Miami-Dade County and Broward County HVHZ.

Series 3100

Push-up, hand chain or electric operation.

Maximum opening width is 16'-0".

Maximum opening height is 20'-0".

26 gauge curtain with windlocks on curtain for all opening widths.

Florida state approval number FL 2274-R2.

Not for use in HVHZ.

Series 750 and **3100** are designed in accordance with the latest editions of ASCE 7, International Building Code and Florida Building Code. Doors have been tested to ASTM E-330.

Series 850-S is designed to comply with the latest edition of the Florida Building Code, including applicable provisions for High Velocity Hurricane Zones (HVHZ). Door has been tested to TAS 201, TAS 202 and TAS 203.

Series 850 is designed to comply with the Miami-Dade County Product Control Division for the High Velocity Hurricane Zone (HVHZ) of the Florida Building Code. Door has been tested to TAS 201, TAS 202 and TAS 203.